FUSION 18 FIREPLACE INSERT





FUSION 18

≎EPA 2020



SPECIFICATIONS	Heat Capacity	1,500 square feet	Certifications	EPA 28R, ASTM E2780, ASTM E2515, CSA B415.1-10, UL 1482 and ULC S628
	Max. Heat Output	75,000 BTUs	Emissions	1.9 g/h
	EPA Firebox Size	1.8 cubic feet	Glass Dimensions	19¼" x 11¼"
	Chimney Liner	5 inch (The use of a 5½ inch or 6 inch liner is possible)*	Patent Numbers	7/325,547 & 9/476,593

^{*}Adapter required



Patented Automatic Air Control

This patented, user-friendly mechanism automatically reduces the amount of combustion air introduced during ignition to the desired burn rate setting. The result is a beautifully consistent fire burning to its full capacity.



Circulating Chamber

The patented adjustable circulating chamber is designed to prevent heat escaping from the existing chimney and allows for an optimal flow and heat transfer.



Premium Quality Blowers (110 CFM)

As an optiont, this powerful yet whisperquiet system effortlessly distributes heat over significant distances. As the combustion progresses, the high-quality blower automatically activates and is set using the variable speed controller.



Stainless Steel Surround

The Fusion fireplace also comes in a beautiful stainless steel surround option.




Built-In Barbecue Grill


This exceptional feature offers the ability to create meals imbued with flavorful smokiness inside the comfort or your own home. Simply drop down the grill once the wood has reduced to embers and place your food inside; the result is memorable barbecued dishes all year-round.




Innovative Baffle Design

Our products have a unique design that allows secondary air to enter through a perforated baffle offering an unimpeded viewing area to the fire all while increasing the efficiency and prolonging the combustion.







5 inch liner inside diameter

S





3594 Jarry East, Montreal, Quebec H1Z 2G4 Telephone: 514 593.4722 Toll-free: 1 877 593.4722 Facsimile: 514 593.4424 www.supremem.com | info@supremem.com

Note:

Information and images contained in this catalog are subject to change and should be used for reference only. All installations should be done in accordance to the specifications detailed in the owner's manual.